

[> Home](#) [> Products](#) [> Anchoring Systems](#) [> Metal Anchors](#) [> Externally Threaded Anchors](#) [> HUS Screw Anchor](#)  
[> HUS-H Universal screw anchor](#) [> HUS-H 10,5 Universal screw anchor](#)

## HUS-H 10.5X65/5/15: Item No.: 00335083



### Technical Data

Anchor length	65 mm
Anchor type	Screw anchor
Working principle	Undercut/keying
Approvals	ETA, Fire IBMB
Environmental conditions	Inside dry
Base materials	Concrete block (solid), Concrete (cracked)
Type of fixing	Through-fastening
Material composition	Carbon steel
Material coating/plating/finish	Deltatone
Corrosion protection	Deltatone
Head configuration	Hex washer head / AF 13
Required setting tool	SI 100 impact screw driver
Wrench size	13 mm
Max. torque	35 Nm
Hole depth	70 mm
Drill bit diameter	8 mm
Edge distance	50 mm
Baseplate clearance hole	12 mm
Min. thickness of base material	100 mm
Standard embedment depth	60 mm
Max. fixture thickness reduced	15 mm

### Related Products

TE 6-A Cordless rotary hammer  
SI 100 Impact screwdriver

[Back to previous page](#)

## Hilti. Outperform. Outlast.